

Super SAM® 125 Sound Control Membrane

Issue Date: 6/10/2016

Revision Date: 1/10/2017

Version: 2

1. PRODUCT IDENTIFICATION

Product Name: Super SAM® 125 Sound Control Membrane

Other means of identification:

SDS # NACP-005

Product Code: 020020160

Recommended use of the chemical and restrictions on use:

Self-adhering membrane used for waterproofing barrier/sealing systems.

Supplier Details and Address:

National Applied Construction Products, Inc.

3200 Main St.

Akron, OH 44319

Emergency Telephone Number:

Company Phone Number: 1-800-633-4622

Emergency Telephone (24 hr):

INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance: Black pliable solid, rubber

Physical state: Solid

Odor: Slight petroleum

Classification: As defined in the OSHA Hazard Communication Standard, 29 CFR 1910.1200, the products listed below are considered articles and do not require an SDS. In addition, articles are not included in the scope of the Globally Harmonization System (GHS). As such, the GHS labeling elements are not included on this SDS. All components listed for this product are bound within the product. When handled as intended and under normal conditions of use, there is no evidence that any of the ingredients are released in amounts that pose a significant health risk. Although these products are not subject to the OSHA Standard or GHS labeling elements, National Applied Construction Products, Inc. would like to disclose as much health and safety information as possible to ensure that this product is handled and used properly. This SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and be made available for employees and other users of this product. In addition, the recommendations for handling and use of these products should be included in worker training programs. PLEASE SEE SECTION 4 FOR ADDITIONAL FIRST AID INFORMATION.

3. INFORMATION ON INGREDIENTS

| Chemical Name | CAS No. | Weight-% |
|---|------------|----------|
| Petroleum Asphalt | 8052-42-4 | 60-70 |
| Crystalline silica | 14808-60-7 | 10-25 |
| Petroleum distillates, solvent dewaxed heavy paraffinic | 64742-65-0 | <5 |

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

General Advice: If exposed or concerned: Get medical advice/

attention. Under extreme and non-normal circumstances such as extensive cutting, grinding and pulverizing, there is some potential exposure to respirable crystalline silica (quartz). Prolonged and frequent exposure to such conditions could in some instances cause silicosis, a fibrosis of the lungs.

Eye Contact: Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.

Skin Contact: Wash off immediately with water for at least 15 minutes.

Inhalation: Remove to fresh air.

Ingestion: Call a poison center or doctor if you feel unwell. Rinse mouth.

Most important symptoms and effects: Some individuals find this product may cause skin irritation or redness. It may aggravate pre-existing skin conditions. Ingestion can cause irritation, nausea, or stomach distress.

Indication of any immediate medical attention and special treatment needed: Notes to Physician, treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Carbon dioxide (CO₂).

Unsuitable Extinguishing Media: Not determined

Specific Hazards Arising from the Chemical: Product is not flammable

Hazardous Combustion Products: Carbon monoxide. Sulfur oxides. Various hydrocarbons.

Protective Equipment and Precautions for Firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protective equipment as required.

Environmental Precautions: See Section 12 for additional Ecological Information. Avoid release to the environment. See Section 13: DISPOSAL CONSIDERATIONS.

Methods for Containment: Prevent further leakage or spillage if safe to do so.

Methods for Clean-up: Clean up in accordance with all applicable regulations.

Sweep up, pick up and put into an approved waste container for disposal.


7. HANDLING AND STORAGE

Advice on Safe Handling: Handle in accordance with good industrial hygiene and safety practice. Use personal protective equipment as required. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product.

Storage Conditions: Keep container tightly closed in a dry, cool and well-ventilated place. Store in secured area.

Incompatible Materials: None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION



Exposure Guidelines: Exposures at these levels are not expected to occur under normal use. These exposure guidelines are provided as a general method for safe workplace monitoring.

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|----------------------------------|---|---|---|
| Petroleum Asphalt 8052-42-4 | TWA: 0.5 mg/m ³ benzene soluble aerosol fume, inhalable fraction | - | Ceiling: 5 mg/m ³ fume 15 min |
| Crystalline silica 14808-60-7 | TWA: 0.025 mg/m ³ respirable fraction | (vacated) TWA: 0.1 mg/m ³ respirable dust: (30)/(%SiO ₂ + 2) mg/m ³ TWA total dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction | IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust |

Other Information: *Because of product form, exposure to dust or fumes is not expected to occur in normal use.

Engineering Controls: Apply technical measures to comply with the occupational exposure limits. Showers. Eyewash stations.

Eye/Face Protection: Use approved eye protection to avoid eye contact. Refer to 29 CFR 1910.133 for eye and face protection regulations.

Skin and Body Protection: Wear normal working gloves of 100% cotton or leather. Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory Protection: Ensure adequate ventilation, especially in confined areas. In case of insufficient ventilation, wear suitable respiratory equipment. Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations: Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Solid

Appearance: Black pliable solid, rubber

Color: Black

Odor: Slight petroleum

Odor Threshold: Not determined

| Property | Values | Remarks |
|------------------------------|------------------------------------|---------|
| pH | Not applicable due to product form | |
| Melting Point/Freezing Point | Not applicable due to product form | |
| Boiling Point/Boiling Range | Not applicable due to product form | |
| Flash Point | Not applicable due to product form | |
| Evaporation Rate | Not applicable due to product form | |
| Flammability (Solid, Gas) | Not applicable due to product form | |
| Flammability Limits in Air | | |
| Upper Flammability Limits | Not applicable due to product form | |
| Lower Flammability Limit | Not applicable due to product form | |
| Vapor Pressure | Not applicable due to product form | |

| Property | Values | Remarks |
|------------------------------|------------------------------------|---------|
| Vapor Density | Not applicable due to product form | |
| Relative Density | Not applicable due to product form | |
| Water Solubility | Dispersible, not miscible | |
| Solubility in other solvents | Not applicable due to product form | |
| Partition Coefficient | Not applicable due to product form | |
| Auto-ignition Temperature | Not applicable due to product form | |
| Decomposition Temperature | Not applicable due to product form | |
| Kinematic Viscosity | Not applicable due to product form | |
| Dynamic Viscosity | Not applicable due to product form | |
| Explosive Properties | Not an explosive | |
| Oxidizing Properties | Not applicable due to product form | |
| VOC Content | 0.0 g/l | |

10. STABILITY AND REACTIVITY

Reactivity: Not reactive under normal conditions.

Chemical Stability: Stable under recommended storage conditions.

Possibility of Hazardous Reaction: None under normal processing.

Conditions to Avoid: Temperatures over 400°F may cause resin degradation. Keep out of reach of children.

Incompatible Materials: None known based on information supplied.

Hazardous Decomposition Products: Carbon monoxide. Various hydrocarbons. Sulfur oxides.

11. TOXICOLOGICAL INFORMATION

Eye Contact: Avoid contact with eyes

Skin Contact: Some individuals find this product may cause skin irritation or redness. It may aggravate pre-existing skin conditions.

Inhalation: Do not inhale

Ingestion: Ingestion can cause irritation, nausea, or stomach distress.

Component Information: *Because of product form, exposure to dust or fumes is not expected to occur in normal use


| Chemical Name | ATEmix (oral) | ATEmix | Inhalation LC50 |
|----------------------------------|----------------------|-------------------------|-----------------|
| Petroleum Asphalt 8052-42-4 | > 5000 mg/kg (Rat) | > 2000 mg/kg (Rabbit) | - |
| Crystalline silica 14808-60-7 | = 500 mg/kg (Rat) | - | - |

Information on physical, chemical and toxicological effects:

Symptoms: Please see section 4 of this SDS for symptoms.

Carcinogenicity: Crystalline Silica is considered to be a human carcinogen when in respirable form (dust / powder). Because of product form, exposure to dust or fumes is not expected to occur in normal use.

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|----------------------------------|-------|---------|-------|------|
| Crystalline silica 14808-60-7 | A2 | Group 1 | Known | X |



Legend:

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety & Health Administration of the US Department of Labor) X - Present

Numerical measures of toxicity: Not applicable due to form of the product.

12. ECOLOGICAL INFORMATION

Ecotoxicity: Product is not classified as environmentally hazardous.

13. DISPOSAL CONSIDERATIONS

Disposal of Wastes: Disposal should be in accordance with applicable regional, national and local laws and regulations. This product is not regulated as a hazardous waste by the U.S. EPA under the Resource Conservation and Recovery Act (RCRA).

14. TRANSPORT INFORMATION

NOTE: Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT: Not regulated. **IATA:** Not regulated. **IMDG:** Not regulated.

15. REGULATORY INFORMATION

| Chemical Name | TSCA | DSL/ NDSL | EINECS/ LINCS | ENCS |
|---|------|--------------|------------------|---------|
| Petroleum Asphalt | X | X | X | |
| Crystalline silica | X | X | X | Present |
| 1,3-butadiene-styrene block polymer | X | X | | Present |
| Petroleum distillates, solvent dewaxed heavy paraffinic | X | X | X | |

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

| Chemical Name | IECSC | KECL | PICCS | AICS |
|---|-------|---------|-------|------|
| Petroleum Asphalt | X | Present | X | X |
| Crystalline silica | X | Present | X | X |
| 1,3-butadiene-styrene block polymer | X | Present | X | X |
| Petroleum distillates, solvent dewaxed heavy paraffinic | X | Present | X | X |

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

SARA 313: Not applicable.

California Proposition 65: This product contains the following Proposition 65 chemicals.

| Chemical Name | California Proposition 65 |
|---------------------------------|---------------------------|
| Crystalline silica - 14808-60-7 | Carcinogen |

US State Right-to-Know Regulations: This product does not contain any substances regulated under applicable state right-to-know regulations.

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|-----------------------------|------------|---------------|--------------|
| Petroleum Asphalt 8052-42-4 | X | X | X |
| Crystalline silica | X | X | X |

16. OTHER INFORMATION

| NFPA | Health Hazards | Flammability | Instability | Special Hazards |
|------|----------------|--------------|-------------|-----------------|
| | 1 | 1 | 0 | Not Determined |

| HMIS | Health Hazards | Flammability | Physical Hazards | Personal Protection |
|------|----------------|----------------|------------------|---------------------|
| | Not Determined | Not Determined | Not Determined | Not Determined |

Issue Date: May 25, 2016 **Revision Date:** June 10, 2016

Revision Note: New format

Disclaimer: The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet



National Applied Construction Products, Inc.

3200 South Main St. Akron, OH 44319

www.NACproducts.com

800.633.4622 • fax: 330.644.3557

©2020 NAC Products, Inc. All Rights Reserved Rev. 7/20